



DESIGN

Tufted Pile Weight:	30.0 oz. per sq. yd. (1017 g/m2)
Product Type:	Modular-Walk Off
Construction:	Tufted
Minimum Sq. Yd.:	No Minimum
Surface Texture:	Texture Performance Cut & Loop
Gauge:	5/32 (25.2 rows per 10 cm)
Density:	7,448
Weight Density:	223,440
Stitches Per Inch:	10.0 (39.37 per 10 cm)
Finished Pile Thickness:	.145" (3.68 mm)
Dye Method:	Solution Dyed
Backing Material:	EcoFlex ICT
Fiber Type:	Duracolor® Premium Nylon
Pattern Repeat:	Not Applicable
Size:	24" x 24" (.6096 m x .6096 m)
Installation Method:	QuarterTurn
Soil Release Technology:	Sentry Soil Protection
GSA Stain Release Rating:	Pass
Foot Traffic Recommendation TARR:	Severe

SUSTAINABILITY


IAQ Green Label Plus:	CRI Green Label Plus GLP1098
Pre-Consumer Recycled Content:	45%
Post-Consumer Recycled Content:	1%
NSF 140:	EcoFlex ICT - NSF 140 Gold
Declare Label:	Declared

PERFORMANCE


Static:	AATCC-134 Under 3.5 KV
Flammability:	ASTM E 648 Class 1 (Glue Down)
Smoke Density:	ASTM E 662 Less than 450

SERVICE


Warranties:	Lifetime Limited Carpet Tile Warranty, Lifetime Duracolor Stain Warranty, Lifetime Static
-------------	--




859
Walnut
Quickship Available



955
Cobalt
Quickship Available



983
Iron Ore
Quickship Available



989
Obsidian
Quickship Available