



**DESIGN**

Product Type:	<b>Modular-Walk Off</b>
Construction:	<b>Tufted</b>
Minimum Sq. Yd.:	<b>No Minimum</b>
Surface Texture:	<b>Performance Loop Pile</b>
Gauge:	<b>5/32 (25.2 rows per 10 cm)</b>
Density:	<b>6,739</b>
Weight Density:	<b>256,082</b>
Stitches Per Inch:	<b>8.5 (33.46 per 10 cm)</b>
Finished Pile Thickness:	<b>.203" (5.16 mm)</b>
Dye Method:	<b>Solution Dyed</b>
Backing Material:	<b>EcoFlex ICT</b>
Fiber Type:	<b>Duracolor® Premium Nylon</b>
Face Weight:	<b>38.0 oz. per sq. yd. (1288 g/m2)</b>
Pattern Repeat:	<b>Not Applicable</b>
Size:	<b>24" x 24" (.6096 m x .6096 m)</b>
Installation Method:	<b>QuarterTurn, Monolithic, BrickAshlar, VerticalAshlar, MultiDirectional</b>
Soil Release Technology:	<b>Sentry</b>
GSA Stain Release Rating:	<b>Pass</b>
Foot Traffic Recommendation TARR:	<b>Severe</b>

**SUSTAINABILITY**

IAQ Green Label Plus:	<b>Green Label Plus 1098</b>
Pre-Consumer Recycled Content:	<b>44.00</b>
Post-Consumer Recycled Content:	<b>1.00</b>
NSF 140:	<b>Gold</b>
Declare Label:	<b>Declared</b>

**PERFORMANCE**

Static:	<b>AATCC-134 Under 3.5 KV</b>
Flammability:	<b>ASTM E 648 Class 1 (Glue Down)</b>
Smoke Density:	<b>ASTM E 662 Less than 450</b>

**SERVICE**

Warranties:	<b>Lifetime Limited Carpet Tile Warranty, Lifetime Duracolor Stain Warranty, Lifetime Static</b>
-------------	--




989  
Obsidian



983  
Iron Ore



955  
Cobalt



859  
Walnut