



859
Walnut
Quickship Available



955
Cobalt
Quickship Available



983
Iron Ore
Quickship Available



989
Obsidian
Quickship Available

DESIGN

Tufted Pile Weight:	38.0 oz. per sq. yd. (1288 g/m ²)
Product Type:	Modular-Walk Off
Construction:	Tufted
Minimum Sq. Yd.:	No Minimum
Surface Texture:	Performance Loop Pile
Gauge:	5/32 (25.2 rows per 10 cm)
Density:	6,739
Weight Density:	256,082
Stitches Per Inch:	8.5 (33.46 per 10 cm)
Finished Pile Thickness:	.203" (5.16 mm)
Dye Method:	Solution Dyed
Backing Material:	EcoFlex NXT
Fiber Type:	Duracolor® Premium Nylon
Fiber Technology:	Duracolor® by Mohawk Group's Stain Resistant System. Passes GSA requirements for permanent stain resistant carpet.
Pattern Repeat:	Not Applicable
Size:	24" x 24" (.6096 m x .6096 m)
Installation Method:	Quarter Turn, Monolithic, Brick Ashlar, Vertical Ashlar, Multi Directional
GSA Stain Release Rating:	Pass
Stain Release Technology:	Permanent, Built into Fiber
Soil Release Technology:	EcoSentry Soil Protection
Foot Traffic Recommendation TARR:	Severe

SUSTAINABILITY

IAQ Green Label Plus:	CRI Green Label Plus GLP1171
Pre-Consumer Recycled Content:	53%
NSF 140:	EcoFlex NXT - NSF 140 Gold
Declare Label:	Declared Red List Free

PERFORMANCE

Static:	AATCC-134 Under 3.5 KV
Flammability:	ASTM E 648 Class 1 (Glue Down)
Smoke Density:	ASTM E 662 Less than 450

SERVICE

Warranties:	Lifetime Limited Carpet Tile Warranty, Lifetime Duracolor Stain Warranty, Lifetime Static
-------------	---