



DESIGN

Product Type:	Broadloom
Construction:	Tufted
Minimum Sq. Yd.:	No Minimum
Surface Texture:	Cut Pile
Gauge:	5/32 (25.2 rows per 10 cm)
Density:	1,595
Weight Density:	40,355
Stitches Per Inch:	7.3 (28.74 per 10 cm)
Finished Pile Thickness:	.571" (14.50 mm)
Dye Method:	Piece Dyed
Backing Material:	Weldlok®
Fiber Type:	75% SmartStrand with DuPont Sorona Triexta / 25% BCF P.E.T.
Face Weight:	25.3 oz. per sq. yd.
Pattern Repeat:	None
Width:	12' width (3.66 m)
Soil Release Technology:	Sentry Plus
Foot Traffic Recommendation TARR:	Heavy

SUSTAINABILITY

IAQ Green Label Plus:	Green Label Plus 1118
NSF 140:	Gold

PERFORMANCE

Static:	AATCC-134 Under 3.5 KV
Flammability:	ASTM E 648 Class 1 (Glue Down)
Smoke Density:	ASTM E 662 Less than 450

SERVICE


Warranties:	Lifetime Limited Wear Warranty, Lifetime Static
-------------	--



717
Cracked Glaze




727
Gleaming Tan



729
Homestead




732
Adobe



752
Redstone Lasso




819
Shimmer




852
Sumatra Blend




859
Twilight Jungle




872
Molten Penny



879
Rootbeer



929
Frosted Pane



959
Winter Flannel