



DESIGN

Tufted Pile Weight:	25.3 oz. per sq. yd.
Product Type:	Broadloom
Construction:	Tufted
Minimum Sq. Yd.:	No Minimum
Surface Texture:	Cut Pile
Gauge:	5/32 (25.2 rows per 10 cm)
Density:	1,595
Weight Density:	40,355
Stitches Per Inch:	7.3 (28.74 per 10 cm)
Finished Pile Thickness:	.571" (14.50 mm)
Dye Method:	Piece Dyed
Backing Material:	Weldlok®
Fiber Type:	75% SmartStrand with DuPont Sorona Triexta / 25% BCF P.E.T.
Pattern Repeat:	None
Width:	12' width (3.66 m)
Soil Release Technology:	Sentry Plus
Foot Traffic Recommendation TARR:	Heavy

SUSTAINABILITY

IAQ Green Label Plus:	CRI Green Label Plus GLP1118
NSF 140:	Weldlok - NSF 140 Gold

PERFORMANCE

Static:	AATCC-134 Under 3.5 KV
Flammability:	Passes Surface Flammability 16 CFR Part 1630
Smoke Density:	ASTM E 662 Less than 450

SERVICE

Warranties:	Lifetime Limited Wear Warranty, Lifetime Static
-------------	--



717
Cracked Glaze




727
Gleaming Tan



729
Homestead




732
Adobe



752
Redstone Lasso



819
Shimmer




852
Sumatra Blend




859
Twilight Jungle




872
Molten Penny



879
Rootbeer



929
Frosted Pane



959
Winter Flannel