



DESIGN

Product Type:	Broadloom
Construction:	Tufted
Minimum Sq. Yd.:	No Minimum
Surface Texture:	Precision Cut & Loop
Gauge:	1/8 (31.50 rows per 10 cm)
Density:	6,312
Weight Density:	170,424
Stitches Per Inch:	8.7 (34.25 per 10 cm)
Finished Pile Thickness:	.154" (3.91 mm)
Dye Method:	Solution Dyed
Backing Material:	Weldlok®
Fiber Type:	Colorstrand® SD Nylon
Face Weight:	28.0 oz. per sq. yd. (949 g/m2)
Pattern Repeat:	0.5" (W) x 0.67" (L)
Width:	12' width (3.66 m)
Soil Release Technology:	Sentry Soil Protection
Foot Traffic Recommendation TARR:	Moderate

SUSTAINABILITY


IAQ Green Label Plus:	Green Label Plus 8216
Pre-Consumer Recycled Content:	50%
NSF 140:	Gold
Declare Label:	Declared Red List Free

PERFORMANCE

Static:	AATCC-134 Under 3.5 KV
Flammability:	ASTM E 648 Class 1 (Glue Down)
Smoke Density:	ASTM E 662 Less than 450

SERVICE

Warranties:	Lifetime Limited Wear Warranty, Lifetime Limited Colorfastness to Light, 10 Year Limited Colorfastness to Atmospheric Contaminants, 10 Year Limited Stain Warranty, Lifetime Static
-------------	--



145
Desirable



711
Gratifying



721
Satisfying




731
Cherished




758
Contenting



833
Grateful




842
Esteemed



858
Congenial



917
Delightful



934
Appreciated