



**DESIGN**

Tufted Pile Weight:	<b>28.0 oz. per sq. yd. (949 g/m<sup>2</sup>)</b>
Product Type:	<b>Broadloom</b>
Construction:	<b>Tufted</b>
Minimum Sq. Yd.:	<b>No Minimum</b>
Surface Texture:	<b>Precision Cut &amp; Loop</b>
Gauge:	<b>1/8 (31.50 rows per 10 cm)</b>
Density:	<b>6,312</b>
Weight Density:	<b>170,424</b>
Stitches Per Inch:	<b>8.7 (34.25 per 10 cm)</b>
Finished Pile Thickness:	<b>.154" (3.91 mm)</b>
Dye Method:	<b>Solution Dyed</b>
Backing Material:	<b>Weldlok®</b>
Fiber Type:	<b>Colorstrand® SD Nylon</b>
Pattern Repeat:	<b>0.5" (W) x 0.67" (L)</b>
Width:	<b>12' width (3.66 m)</b>
Soil Release Technology:	<b>Sentry Soil Protection</b>
Foot Traffic Recommendation TARR:	<b>Moderate</b>

**SUSTAINABILITY**

IAQ Green Label Plus:	<b>CRI Green Label Plus GLP8216</b>
Pre-Consumer Recycled Content:	<b>50%</b>
NSF 140:	<b>Weldlok - NSF 140 Gold</b>
Declare Label:	<b>Declared Red List Free</b>

**PERFORMANCE**

Static:	<b>AATCC-134 Under 3.5 KV</b>
Flammability:	<b>ASTM E 648 Class 1 (Glue Down)</b>
Smoke Density:	<b>ASTM E 662 Less than 450</b>

**SERVICE**

Warranties:	<b>Lifetime Limited Wear Warranty, Lifetime Limited Colorfastness to Light, 10 Year Limited Colorfastness to Atmospheric Contaminants, 10 Year Limited Stain Warranty, Lifetime Static</b>
-------------	--



145  
Desirable



711  
Gratifying



721  
Satisfying




731  
Cherished




758  
Contenting



833  
Grateful



842  
Esteemed



858  
Congenial



917  
Delightful



934  
Appreciated