



DESIGN

| | |
|-----------------------------------|---|
| Tufted Pile Weight: | 34.0 oz. per sq. yd. (1153 g/m²) |
| Product Type: | Tile |
| Construction: | Tufted |
| Minimum Sq. Yd.: | No Minimum |
| Surface Texture: | Textured Patterned Loop |
| Gauge: | 1/12 (47.00 rows per 10 cm) |
| Density: | 12,929 |
| Weight Density: | 439,586 |
| Stitches Per Inch: | 11.0 (43.31 per 10 cm) |
| Finished Pile Thickness: | .104" (2.64 mm) |
| Dye Method: | Solution Dyed |
| Backing Material: | EcoFlex NXT |
| Fiber Type: | Duracolor® Premium Nylon |
| Fiber Technology: | Duracolor® by Mohawk Group's Stain Resistant System. Passes GSA requirements for permanent stain resistant carpet. |
| Pattern Repeat: | Not Applicable |
| Size: | 24" x 24" (.6096 m x .6096 m) |
| Installation Method: | QuarterTurn, Monolithic, BrickAshlar, VerticalAshlar, MultiDirectional |
| Soil Release Technology: | Sentry Soil Protection |
| Foot Traffic Recommendation TARR: | Heavy |



364
Wine




454
Lavender



556
Blue



575
Navy



656
Green



846
Teak



869
Medium Taupe



889
Dark Taupe



929
Light Grey

SUSTAINABILITY

| | |
|---------------------------------|-------------------------------------|
| IAQ Green Label Plus: | CRI Green Label Plus GLP1171 |
| Pre-Consumer Recycled Content: | 56% |
| Post-Consumer Recycled Content: | 1% |
| NSF 140: | EcoFlex NXT - NSF 140 Gold |
| Declare Label: | Declared Red List Free |

PERFORMANCE

| | |
|----------------|---------------------------------------|
| Static: | AATCC-134 Under 3.5 KV |
| Flammability: | ASTM E 648 Class 1 (Glue Down) |
| Smoke Density: | ASTM E 662 Less than 450 |

SERVICE

| | |
|-------------|--|
| Warranties: | Lifetime Limited Carpet Tile Warranty, Lifetime Duracolor Stain Warranty, Lifetime Static |
|-------------|--|



955
Medium Cool Grey



968
Medium Grey



979
Black



985
Dark Cool Grey



989
Dark Grey