



DESIGN

Product Type:	Tile
Construction:	Tufted
Minimum Sq. Yd.:	No Minimum
Surface Texture:	Textured Patterned Loop
Gauge:	1/12 (47.00 rows per 10 cm)
Density:	6,776
Weight Density:	108,423
Stitches Per Inch:	11.0 (43.31 per 10 cm)
Finished Pile Thickness:	.085" (2.16 mm)
Dye Method:	Solution Dyed
Backing Material:	EcoFlex ICT
Fiber Type:	Colorstrand® SD Nylon
Face Weight:	16.0 oz. per sq. yd. (542 g/m2)
Pattern Repeat:	Not Applicable
Size:	12" x 36" (.3048 m x .9144 m)
Installation Method:	HalfLap, BrickAshlar, BasketWeave, PlankHalfLap, MonolithicStepping, Random, Herringbone
Soil Release Technology:	Sentry Soil Protection
Foot Traffic Recommendation TARR:	Severe

SUSTAINABILITY

IAQ Green Label Plus:	Green Label Plus 1098
Pre-Consumer Recycled Content:	48%
NSF 140:	Gold
Declare Label:	Declared

PERFORMANCE


Static:	AATCC-134 Under 3.5 KV
Flammability:	ASTM E 648 Class 1 (Glue Down)
Smoke Density:	ASTM E 662 Less than 450

SERVICE


Warranties:	Lifetime Limited Carpet Tile Warranty, Lifetime Limited Colorfastness to Light, 10 Year Limited Colorfastness to Atmospheric Contaminants, 10 Year Limited Stain Warranty, Lifetime Static
-------------	--




152
Unite



358
Weave




565
Cable




751
Intermingle




859
Link




862
Spin



883
Entwine



955
Lace



983
Bind



999
Connect