



DESIGN

| | |
|-----------------------------------|--|
| Product Type: | Tile |
| Construction: | Tufted |
| Minimum Sq. Yd.: | No Minimum |
| Surface Texture: | Textured Patterned Loop |
| Gauge: | 1/12 (47.00 rows per 10 cm) |
| Density: | 6,545 |
| Weight Density: | 104,720 |
| Stitches Per Inch: | 11.5 (45.28 per 10 cm) |
| Finished Pile Thickness: | .088" (2.23 mm) |
| Dye Method: | Solution Dyed |
| Backing Material: | EcoFlex ICT |
| Fiber Type: | Colorstrand® SD Nylon |
| Face Weight: | 16.0 oz. per sq. yd. (542 g/m2) |
| Pattern Repeat: | Not Applicable |
| Size: | 12" x 36" (.3048 m x .9144 m) |
| Installation Method: | HalfLap, BrickAshlar, BasketWeave, PlankHalfLap, MonolithicStepping, Random, Herringbone |
| Soil Release Technology: | Sentry Soil Protection |
| Foot Traffic Recommendation TARR: | Severe |

SUSTAINABILITY


| | |
|--------------------------------|-----------------------|
| IAQ Green Label Plus: | Green Label Plus 1098 |
| Pre-Consumer Recycled Content: | 48% |
| NSF 140: | Gold |
| Declare Label: | Declared |

PERFORMANCE

| | |
|----------------|--------------------------------|
| Static: | AATCC-134 Under 3.5 KV |
| Flammability: | ASTM E 648 Class 1 (Glue Down) |
| Smoke Density: | ASTM E 662 Less than 450 |

SERVICE


| | |
|-------------|--|
| Warranties: | Lifetime Limited Carpet Tile Warranty, Lifetime Limited Colorfastness to Light, 10 Year Limited Colorfastness to Atmospheric Contaminants, 10 Year Limited Stain Warranty, Lifetime Static |
|-------------|--|



152
Unite



358
Weave




565
Cable




751
Intermingle




859
Link




862
Spin



883
Entwine



955
Lace



983
Bind



999
Connect