



DESIGN

Tufted Pile Weight:	16.0 oz. per sq. yd. (542 g/m²)
Product Type:	Broadloom
Construction:	Tufted
Minimum Sq. Yd.:	No Minimum
Surface Texture:	Textured Patterned Loop
Gauge:	1/12 (47.00 rows per 10 cm)
Density:	6,695
Weight Density:	107,120
Stitches Per Inch:	13.8 (54.37 per 10 cm)
Finished Pile Thickness:	.087" (2.21 mm)
Dye Method:	Solution Dyed
Backing Material:	Unibond® Plus
Fiber Type:	Colorstrand® SD Nylon
Pattern Repeat:	18" (W) x 29.5" (L)
Width:	12' width (3.66 m)
Soil Release Technology:	Sentry Soil Protection
Foot Traffic Recommendation TARR:	Heavy

SUSTAINABILITY


IAQ Green Label Plus:	CRI Green Label Plus GLP3802
Pre-Consumer Recycled Content:	38%
NSF 140:	Unibond Plus - NSF 140 Gold
Declare Label:	Declared Red List Free

PERFORMANCE


Static:	AATCC-134 Under 3.5 KV
Flammability:	ASTM E 648 Class 1 (Glue Down)
Smoke Density:	ASTM E 662 Less than 450

SERVICE

Warranties:	Lifetime Limited Unibond® Plus Warranty, Lifetime Limited Colorfastness to Light, 10 Year Limited Colorfastness to Atmospheric Contaminants, 10 Year Limited Stain Warranty, Lifetime Static
-------------	---



152
Patinaed Brass
Quickship Available




358
Galvanized Steel
Quickship Available




751
Metal Foil
Quickship Available



859
Salvaged Find
Quickship Available




862
Burnished Bronze
Quickship Available



883
Corrugated Suede
Quickship Available



955
Perforated Tin
Quickship Available



983
Polished Silver
Quickship Available



999
Oxidized Iron
Quickship Available