



DESIGN

| | |
|-----------------------------------|--|
| Product Type: | Broadloom |
| Construction: | Tufted |
| Minimum Sq. Yd.: | No Minimum |
| Surface Texture: | Textured Patterned Loop |
| Gauge: | 1/12 (47.00 rows per 10 cm) |
| Density: | 6,695 |
| Weight Density: | 107,120 |
| Stitches Per Inch: | 13.8 (54.37 per 10 cm) |
| Finished Pile Thickness: | .087" (2.21 mm) |
| Dye Method: | Solution Dyed |
| Backing Material: | Unibond® Plus |
| Fiber Type: | Colorstrand® SD Nylon |
| Face Weight: | 16.0 oz. per sq. yd. (542 g/m2) |
| Pattern Repeat: | 18" (W) x 29.5" (L) |
| Width: | 12' width (3.66 m) |
| Soil Release Technology: | Sentry Soil Protection |
| Foot Traffic Recommendation TARR: | Heavy |

SUSTAINABILITY


| | |
|--------------------------------|-------------------------------|
| IAQ Green Label Plus: | Green Label Plus 3802 |
| Pre-Consumer Recycled Content: | 38% |
| NSF 140: | Gold |
| Declare Label: | Declared Red List Free |

PERFORMANCE

| | |
|----------------|---------------------------------------|
| Static: | AATCC-134 Under 3.5 KV |
| Flammability: | ASTM E 648 Class 1 (Glue Down) |
| Smoke Density: | ASTM E 662 Less than 450 |

SERVICE

| | |
|-------------|---|
| Warranties: | Lifetime Limited Unibond® Plus Warranty, Lifetime Limited Colorfastness to Light, 10 Year Limited Colorfastness to Atmospheric Contaminants, 10 Year Limited Stain Warranty, Lifetime Static |
|-------------|---|



152
Patinaed Brass




358
Galvanized Steel




751
Metal Foil




859
Salvaged Find



862
Burnished Bronze



883
Corrugated Suede



955
Perforated Tin



983
Polished Silver



999
Oxidized Iron