



### DESIGN

Tufted Pile Weight:	<b>16.0 oz. per sq. yd. (542 g/m<sup>2</sup>)</b>
Product Type:	<b>Broadloom</b>
Construction:	<b>Tufted</b>
Minimum Sq. Yd.:	<b>No Minimum</b>
Surface Texture:	<b>Textured Patterned Loop</b>
Gauge:	<b>1/12 (47.00 rows per 10 cm)</b>
Density:	<b>10,105</b>
Weight Density:	<b>161,684</b>
Stitches Per Inch:	<b>12.7 (50.00 per 10 cm)</b>
Finished Pile Thickness:	<b>.057" (1.44 mm)</b>
Dye Method:	<b>Solution Dyed</b>
Backing Material:	<b>Unibond® Plus</b>
Fiber Type:	<b>Colorstrand® SD Nylon</b>
Pattern Repeat:	<b>18" (W) x 29.5" (L)</b>
Width:	<b>12' width (3.66 m)</b>
Soil Release Technology:	<b>Sentry Soil Protection</b>
Foot Traffic Recommendation TARR:	<b>Heavy</b>

### SUSTAINABILITY


IAQ Green Label Plus:	<b>CRI Green Label Plus GLP3802</b>
Pre-Consumer Recycled Content:	<b>38%</b>
NSF 140:	<b>Unibond Plus - NSF 140 Gold</b>
Declare Label:	<b>Declared Red List Free</b>

### PERFORMANCE

Static:	<b>AATCC-134 Under 3.5 KV</b>
Flammability:	<b>ASTM E 648 Class 1 (Glue Down)</b>
Smoke Density:	<b>ASTM E 662 Less than 450</b>

### SERVICE

Warranties:	<b>Lifetime Limited Unibond® Plus Warranty, Lifetime Limited Colorfastness to Light, 10 Year Limited Colorfastness to Atmospheric Contaminants, 10 Year Limited Stain Warranty, Lifetime Static</b>
-------------	---



152  
Patinaed Brass  
Quickship Available




358  
Galvanized Steel  
Quickship Available



751  
Metal Foil  
Quickship Available



859  
Salvaged Find  
Quickship Available



862  
Burnished Bronze  
Quickship Available



883  
Corrugated Suede  
Quickship Available



955  
Perforated Tin  
Quickship Available



983  
Polished Silver  
Quickship Available



999  
Oxidized Iron  
Quickship Available