



**DESIGN**

Product Type:	Broadloom
Construction:	Tufted
Minimum Sq. Yd.:	No Minimum
Surface Texture:	Level Loop
Gauge:	1/10 (39.37 rows per 10 cm)
Density:	4,716
Weight Density:	56,592
Stitches Per Inch:	9.0 (35.43 per 10 cm)
Finished Pile Thickness:	.099" (2.51 mm)
Dye Method:	Solution Dyed
Backing Material:	Weldlok®
Fiber Type:	EnviroStrand™ PET
Face Weight:	12.0 oz. per sq. yd. (407 g/m2)
Pattern Repeat:	None
Width:	12' width (3.66 m)
Soil Release Technology:	Sentry Plus
Foot Traffic Recommendation TARR:	Heavy

**SUSTAINABILITY**


IAQ Green Label Plus:	Green Label Plus 0350
Pre-Consumer Recycled Content:	1.00
Post-Consumer Recycled Content:	27.00
Declare Label:	Declared Red List Free

**PERFORMANCE**

Static:	AATCC-134 Under 3.5 KV
Flammability:	ASTM E 648 Class 1 (Glue Down)
Smoke Density:	ASTM E 662 Less than 450

**SERVICE**


Warranties:	10 Year Limited Wear Warranty, 10 Year Limited Static Protection Warranty, 10 Year Stain Resistance Warranty, 10 Year Limited Colorfastness to Light, 10 Year Limited Colorfastness to Atmospheric Contaminants
-------------	---




383  
Clay




589  
Cobalt




748  
Praline



852  
Chestnut




869  
Hickory



889  
Walnut



949  
Pewter



959  
Nickel



979  
Charcoal



999  
Onyx