



**DESIGN**

Tufted Pile Weight:	<b>12.0 oz. per sq. yd. (407 g/m2)</b>
Product Type:	<b>Broadloom</b>
Construction:	<b>Tufted</b>
Minimum Sq. Yd.:	<b>No Minimum</b>
Surface Texture:	<b>Level Loop</b>
Gauge:	<b>1/10 (39.37 rows per 10 cm)</b>
Density:	<b>4,716</b>
Weight Density:	<b>56,592</b>
Stitches Per Inch:	<b>9.0 (35.43 per 10 cm)</b>
Finished Pile Thickness:	<b>.099" (2.51 mm)</b>
Dye Method:	<b>Solution Dyed</b>
Backing Material:	<b>Weldlok®</b>
Fiber Type:	<b>EnviroStrand™ PET</b>
Pattern Repeat:	<b>None</b>
Width:	<b>12' width (3.66 m)</b>
Soil Release Technology:	<b>Sentry Plus</b>
Foot Traffic Recommendation TARR:	<b>Heavy</b>

**SUSTAINABILITY**


IAQ Green Label Plus:	<b>CRI Green Label Plus GLP0350</b>
Pre-Consumer Recycled Content:	<b>1%</b>
Post-Consumer Recycled Content:	<b>27%</b>
Declare Label:	<b>Declared Red List Free</b>

**PERFORMANCE**

Static:	<b>AATCC-134 Under 3.5 KV</b>
Flammability:	<b>ASTM E 648 Class 1 (Glue Down)</b>
Smoke Density:	<b>ASTM E 662 Less than 450</b>

**SERVICE**


Warranties:	<b>10 Year Limited Wear Warranty, 10 Year Limited Static Protection Warranty, 10 Year Stain Resistance Warranty, 10 Year Limited Colorfastness to Light, 10 Year Limited Colorfastness to Atmospheric Contaminants</b>
-------------	--




383  
Clay  
Quickship Available




589  
Cobalt  
Quickship Available




748  
Praline  
Quickship Available



852  
Chestnut  
Quickship Available



869  
Hickory  
Quickship Available




889  
Walnut  
Quickship Available



949  
Pewter  
Quickship Available



959  
Nickel  
Quickship Available



979  
Charcoal  
Quickship Available



999  
Onyx  
Quickship Available