



**DESIGN**

Product Type:	<b>Broadloom</b>
Construction:	<b>Tufted</b>
Minimum Sq. Yd.:	<b>No minimum, some colors available in 15' width</b>
Surface Texture:	<b>Level Loop</b>
Gauge:	<b>1/10 (39.37 rows per 10 cm)</b>
Density:	<b>5,592</b>
Weight Density:	<b>111,840</b>
Stitches Per Inch:	<b>12.4 (48.82 per 10 cm)</b>
Finished Pile Thickness:	<b>.137" (3.48 mm)</b>
Dye Method:	<b>Solution Dyed</b>
Backing Material:	<b>Weldlok®</b>
Fiber Type:	<b>EnviroStrand™ PET</b>
Face Weight:	<b>20.0 oz. per sq. yd. (678 g/m2)</b>
Pattern Repeat:	<b>None</b>
Width:	<b>12' width (3.66 m)</b>
Soil Release Technology:	<b>Sentry Plus</b>
Foot Traffic Recommendation TARR:	<b>Heavy</b>

**SUSTAINABILITY**


IAQ Green Label Plus:	<b>Green Label Plus 0350</b>
Pre-Consumer Recycled Content:	<b>1%</b>
Post-Consumer Recycled Content:	<b>37%</b>
Declare Label:	<b>Declared Red List Free</b>

**PERFORMANCE**

Static:	<b>AATCC-134 Under 3.5 KV</b>
Flammability:	<b>ASTM E 648 Class 1 (Glue Down)</b>
Smoke Density:	<b>ASTM E 662 Less than 450</b>

**SERVICE**


Warranties:	<b>10 Year Limited Wear Warranty, 10 Year Limited Static Protection Warranty, 10 Year Stain Resistance Warranty, 10 Year Limited Colorfastness to Light, 10 Year Limited Colorfastness to Atmospheric Contaminants</b>
-------------	------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------




383  
Clay




589  
Cobalt




748  
Praline



852  
Chestnut




869  
Hickory



889  
Walnut



949  
Pewter



959  
Nickel



979  
Charcoal



999  
Onyx