



DESIGN

Tufted Pile Weight:	20.0 oz. per sq. yd. (678 g/m²)
Product Type:	Broadloom
Construction:	Tufted
Minimum Sq. Yd.:	No minimum, some colors available in 15' width
Surface Texture:	Level Loop
Gauge:	1/10 (39.37 rows per 10 cm)
Density:	5,592
Weight Density:	111,840
Stitches Per Inch:	12.4 (48.82 per 10 cm)
Finished Pile Thickness:	.137" (3.48 mm)
Dye Method:	Solution Dyed
Backing Material:	Weldlok®
Fiber Type:	EnviroStrand™ PET
Pattern Repeat:	None
Width:	12' width (3.66 m)
Soil Release Technology:	Sentry Plus
Foot Traffic Recommendation TARR:	Heavy

SUSTAINABILITY


IAQ Green Label Plus:	CRI Green Label Plus GLP0350
Pre-Consumer Recycled Content:	1%
Post-Consumer Recycled Content:	37%
Declare Label:	Declared Red List Free

PERFORMANCE


Static:	AATCC-134 Under 3.5 KV
Flammability:	ASTM E 648 Class 1 (Glue Down)
Smoke Density:	ASTM E 662 Less than 450

SERVICE


Warranties:	10 Year Limited Wear Warranty, 10 Year Limited Static Protection Warranty, 10 Year Stain Resistance Warranty, 10 Year Limited Colorfastness to Light, 10 Year Limited Colorfastness to Atmospheric Contaminants
-------------	--




383
Clay
Quickship Available




589
Cobalt
Quickship Available




748
Praline
Quickship Available



852
Chestnut
Quickship Available




869
Hickory
Quickship Available




889
Walnut
Quickship Available



949
Pewter
Quickship Available



959
Nickel
Quickship Available



979
Charcoal
Quickship Available



999
Onyx
Quickship Available