



DESIGN

Product Type:	Broadloom
Construction:	Tufted
Minimum Sq. Yd.:	No minimum, some colors available in 15' width
Surface Texture:	Level Loop
Gauge:	1/10 (39.37 rows per 10 cm)
Density:	5,592
Weight Density:	111,840
Stitches Per Inch:	12.4 (48.82 per 10 cm)
Finished Pile Thickness:	.137" (3.48 mm)
Dye Method:	Solution Dyed
Backing Material:	Weldlok®
Fiber Type:	EnviroStrand™ PET
Face Weight:	20.0 oz. per sq. yd. (678 g/m2)
Pattern Repeat:	None
Width:	12' width (3.66 m)
Soil Release Technology:	Sentry Plus
Foot Traffic Recommendation TARR:	Heavy

SUSTAINABILITY


IAQ Green Label Plus:	CRI Green Label Plus GLP0350
Pre-Consumer Recycled Content:	1%
Post-Consumer Recycled Content:	37%
Declare Label:	Declared Red List Free

PERFORMANCE

Static:	AATCC-134 Under 3.5 KV
Flammability:	ASTM E 648 Class 1 (Glue Down)
Smoke Density:	ASTM E 662 Less than 450

SERVICE


Warranties:	10 Year Limited Wear Warranty, 10 Year Limited Static Protection Warranty, 10 Year Stain Resistance Warranty, 10 Year Limited Colorfastness to Light, 10 Year Limited Colorfastness to Atmospheric Contaminants
-------------	--




383
Clay




589
Cobalt




748
Praline



852
Chestnut




869
Hickory



889
Walnut



949
Pewter



959
Nickel



979
Charcoal



999
Onyx