



DESIGN

Product Type:	Tile
Construction:	Tufted
Minimum Sq. Yd.:	No Minimum
Surface Texture:	Textured Patterned Loop
Gauge:	1/12 (47.00 rows per 10 cm)
Density:	8,164
Weight Density:	179,628
Stitches Per Inch:	11.4 (44.88 per 10 cm)
Finished Pile Thickness:	.097" (2.46 mm)
Dye Method:	Solution Dyed / Yarn Dyed
Backing Material:	EcoFlex NXT
Fiber Type:	Duracolor® Premium Nylon
Fiber Technology:	Duracolor® by Mohawk Group's Stain Resistant System. Passes GSA requirements for permanent stain resistant carpet.
Face Weight:	22.0 oz. per sq. yd. (746 g/m ²)
Pattern Repeat:	Not Applicable
Size:	24" x 24" (.6096 m x .6096 m)
Installation Method:	QuarterTurn, BrickAshlar, VerticalAshlar, MultiDirectional
Soil Release Technology:	Sentry
GSA Stain Release Rating:	Pass
Foot Traffic Recommendation TARR:	Severe

SUSTAINABILITY

IAQ Green Label Plus:	Green Label Plus 1171
Pre-Consumer Recycled Content:	56%
Post-Consumer Recycled Content:	1%
NSF 140:	Gold
Declare Label:	Declared Red List Free

PERFORMANCE


Static:	AATCC-134 Under 3.5 KV
Flammability:	ASTM E 648 Class 1 (Glue Down)
Smoke Density:	ASTM E 662 Less than 450

SERVICE

Warranties:	Lifetime Limited Carpet Tile Warranty, Lifetime Duracolor Stain Warranty, Lifetime Static
-------------	---



138
Oasis



173
Composure



245
Aura



579
Harmony



637
Sense



855
Zen



856
Essence



966
Tranquil