


**DESIGN**

|                                   |  |
|-----------------------------------|--|
| Product Type:                     | Tile   |
| Construction:                     | Tufted   |
| Minimum Sq. Yd.:                  | No Minimum   |
| Surface Texture:                  | Textured Patterned Loop  |
| Gauge:                            | 1/12 (47.00 rows per 10 cm)  |
| Density:                          | 9,000  |
| Weight Density:                   | 198,000  |
| Stitches Per Inch:                | 12.2 (48.03 per 10 cm)   |
| Finished Pile Thickness:          | .088" (2.23 mm)  |
| Dye Method:                       | Solution Dyed / Yarn Dyed  |
| Backing Material:                 | EcoFlex NXT  |
| Fiber Type:                       | Duracolor® Premium Nylon   |
| Fiber Technology:                 | Duracolor® by Mohawk Group's Stain Resistant System. Passes GSA requirements for permanent stain resistant carpet. |
| Face Weight:                      | 22.0 oz. per sq. yd. (746 g/m <sup>2</sup> )   |
| Pattern Repeat:                   | Not Applicable   |
| Size:                             | 24" x 24" (.6096 m x .6096 m)  |
| Installation Method:              | QuarterTurn, BrickAshlar, VerticalAshlar, MultiDirectional   |
| Soil Release Technology:          | Sentry Soil Protection   |
| GSA Stain Release Rating:         | Pass   |
| Foot Traffic Recommendation TARR: | Severe   |



138  
Oasis



173  
Composure




245  
Aura



579  
Harmony



637  
Sense



855  
Zen



856  
Essence



966  
Tranquil

**SUSTAINABILITY**

|                                 |                        |
|---------------------------------|------------------------|
| IAQ Green Label Plus:           | Green Label Plus 1171  |
| Pre-Consumer Recycled Content:  | 56%                    |
| Post-Consumer Recycled Content: | 1%                     |
| NSF 140:                        | Gold                   |
| Declare Label:                  | Declared Red List Free |

**PERFORMANCE**

|                |                                |
|----------------|--------------------------------|
| Static:        | AATCC-134 Under 3.5 KV         |
| Flammability:  | ASTM E 648 Class 1 (Glue Down) |
| Smoke Density: | ASTM E 662 Less than 450       |

**SERVICE**

|             |   |
|-------------|---|
| Warranties: | Lifetime Limited Carpet Tile Warranty, Lifetime Duracolor Stain Warranty, Lifetime Static |
|-------------|---|