Mohawk Group

Clic Step 20 mil Collection







378

879

Warehouse

State House



258 Light Rail



786 Boulevard



848 Industrial



332

Trolley

White Noise

DESIGN

Product Type: Floating LVT .16" (4mm) Gauge: Wear Layer: 20 mil (0.5mm)

Finish: M-Force Enhanced Urethane

Edge Profile: Microbevel 7"x48" (nominal) Size: Surface Profile: Wood Emboss

Anti-Microbial:

Installation: Floating with Uniclic Locking System

Recommended Adhesive: None Required

Square Feet Per Carton: 22.14 sf/ctn (2.05 m²/ctn)

Pieces Per Carton: 10 pcs/ctn

Pounds per carton: 25.13 lbs/ctn (11.39 kg/ctn) Underlayment: Mohawk ActiveSound

PERFORMANCE

Construction: **Commercial Grade Floating Resilient Tile** ASTM F1700 - Class III, Type A - Smooth, Type B -Classification:

ASTM E662 - Passes - < 450 (non-flaming) Smoke Density: Squareness: ASTM F2055 - Passes - 0.010 in. max

Size and Tolerance: ASTM F2055 - Passes - ±0.016 in. per linear foot ASTM F2199 - Passes - 0.15% max (0.020 in. per Dimensional Stability:

ASTM F386 - Passes - 0.157±0.005 in. Thickness:

(4.0±0.13mm)

Flexibility: ASTM F137 - Passes - \leq 1.0 in., no cracks or breaks

Static Load: ASTM F970 - Passes, modified - 1000 psi Residual Indentation: ASTM F1914 - Passes - Average less than 8% ASTM D2047 - Passes - > 0.6 Wet, 0.6 Dry Slip Resistance:

Resistance To Chemicals: ASTM F925 - Passes - No Change or Slight Change

Resistance To Heat: ASTM F1514 - Passes - $\Delta E \le 5$ ASTM F1515 - Passes - $\Delta E \le 5$ Resistance To Light:

Critical Radiant Flux: ASTM E648 - Passes - Minimum 0.7 Watt

SUSTAINABILITY

Certification: FloorScore® certified

SERVICE

Warranties: Limited 10 Year Commercial



Clic Step 20 mil Collection







929 Skyscraper



934 Tracks



948 Loft



999 Wrought Iron