



DESIGN

Product Type:	Glue Down LVT
Gauge:	.10" (2.5mm)
Wear Layer:	12 mil (0.3mm)
Finish:	M-Force Enhanced Urethane
Surface Profile:	Wood Emboss
Size:	6" W x 48" L (152.4 mm x 1219.2 mm)
Square Feet Per Carton:	36 sf/ctn (3.34 m ² /ctn)
Pieces Per Carton:	18 pcs/ctn
Pounds per carton:	34.17 lbs/ctn (15.49 kg/ctn)
Installation Method:	Glue Down
Recommended Adhesive:	Mohawk M95.0 Resilient Flooring Adhesive, MS160 Spray, M700 Pressure Sensitive Adhesive
Underlayment:	Mohawk Accusound

PERFORMANCE

Construction:	Light Commercial Grade Resilient Tile
Classification:	ASTM F1700 - Class III, Type A - Smooth, Type B - Embossed
Squareness:	ASTM F2055 - Passes - ±0.010 in. max
Size and Tolerance:	ASTM F2055 - Passes - ±0.024 in. per linear foot
Thickness:	ASTM F386 - Passes - ±0.005 in.
Flexibility:	ASTM F137 - Passes - ≤ 1.0 in., no cracks or breaks
Dimensional Stability:	ASTM F2199 - Passes - 6hrs@180F, 0.12%
Static Load:	ASTM F970 - Passes, modified - 1500 psi
Residual Indentation:	ASTM F1914 - Passes - Average less than 8%
Slip Resistant:	ASTM D2047 - Passes - > 0.6 Wet, 0.6 Dry
Resistance To Chemicals:	ASTM F925 - Passes - No Change or Slight Change
Resistance To Light:	ASTM F1515 - Passes - ΔE ≤ 8
Resistance To Heat:	ASTM F1514 - Passes - ΔE ≤ 8
Critical Radiant Flux:	ASTM E648 - Passes - ≥ 0.45 watts/cm ² , Class 1
Smoke Density:	ASTM E662 - Passes

SUSTAINABILITY


Certification:	FloorScore® certified
----------------	-----------------------

SERVICE

Warranties:	Limited 10 Year Commercial
-------------	----------------------------




111
Northern Whites




132
Hayday




143
Beech Blonde




328
Rusticated




332
Carmello




343
Cherrytale



362
Red My Mind



873
Safe Arbor



883
Brownie Points



921
Shore Thing



933
Silver Fox



959
Grey Matters