

Global Entry Collection



DESIGN

Product Type:	Glue Down LVT
Gauge:	.10" (2.5mm)
Wear Layer:	20 mil (0.5mm)
Finish:	M-Force Enhanced Urethane
Size:	12" x 24"
Square Feet Per Carton:	36 sf/ctn (3.34 m ² /ctn)
Pieces Per Carton:	18 pcs/ctn
Pounds per carton:	34.03 lbs/ctn (15.43 kg/ctn)
Installation Method:	Glue Down
Recommended Adhesive:	M95.0 Resilient Flooring Adhesive, MS160 Spray, M700 Pressure Sensitive Adhesive

PERFORMANCE


Construction:	Commercial Grade Resilient Tile
Classification:	ASTM F1700 - Class III, Type A - Smooth, Type B - Embossed
Squareness:	ASTM F2055 - Passes - 0.010 in. max
Size and Tolerance:	ASTM F2055 - Passes - Width: 304.8mm±0.44mm; Length: 609.6mm±0.8mm
Thickness:	ASTM F386 - Passes - As specified 2.5mm ±0.13mm
Dimensional Stability:	ASTM F1237 - Passes - Controlled within Width±0.005 in.: 304.8mm±0.39mm; Length: 609.6mm±0.8mm
Static Load:	ASTM F970 - Passes, modified - 1500 psi
Residual Indentation:	ASTM F1914 - Passes - Average less than 8%
Slip Resistant:	ASTM D2047 - Passes - > 0.6 Wet, 0.6 Dry
Resistance To Chemicals:	ASTM F925 - Passes - No Change or Slight Change
Resistance To Light:	ASTM F1515 - Passes - ΔE ≤ 8
Resistance To Heat:	ASTM F1514 - Passes - ΔE ≤ 8
Critical Radiant Flux:	ASTM E648 - Passes - ≥ 0.45 watts/cm ² , Class 1
Smoke Density:	ASTM E662 - Passes

SUSTAINABILITY

Certification:	FloorScore® certified
Biobased Material Content:	8%

SERVICE


Warranties:	Limited 10 Year Commercial
-------------	----------------------------




646
Green Grass



555
Blue Night



453
Vivid Violet



353
Red Hot



252
Outrageous Orange



121
Unmellow Yellow



123
Barely Beige



133
Totally Tan



858
Bronze Blast

Global Entry Collection



378
Chocolate Bar



976
Blackout



959
Grey Granite



927
Sonic Silver



926
Agreeable Grey



915
Frostbite