




646  
Green Grass



555  
Blue Night



453  
Vivid Violet



353  
Red Hot



252  
Outrageous Orange



121  
Unmellow Yellow



123  
Barely Beige



133  
Totally Tan



858  
Bronze Blast

**DESIGN**

Product Type:	Glue Down LVT
Gauge:	.10" (2.5mm)
Wear Layer:	20 mil (0.5mm)
Finish:	M-Force Enhanced Urethane
Size:	12" x 24"
Anti-Microbial:	No
Installation:	Glue Down
Recommended Adhesive:	M95.0 Resilient Flooring Adhesive, MS160 Spray, M700 Pressure Sensitive Adhesive
Square Feet Per Carton:	36 sf/ctn (3.34 m <sup>2</sup> /ctn)
Pieces Per Carton:	18 pcs/ctn
Pounds per carton:	34.03 lbs/ctn (15.43 kg/ctn)

**PERFORMANCE**

Construction:	Commercial Grade Resilient Tile
Classification:	ASTM F1700 - Class III, Type A - Smooth, Type B - Embossed
Smoke Density:	ASTM E662 - Passes
Squareness:	ASTM F2055 - Passes - 0.010 in. max
Size and Tolerance:	ASTM F2055 - Passes - Width: 304.8mm±0.44mm; Length: 609.6mm±0.8mm
Dimensional Stability:	ASTM F1237 - Passes - Controlled within Width±0.005 in.: 304.8mm±0.39mm; Length: 609.6mm±0.8mm
Thickness:	ASTM F386 - Passes - As specified 2.5mm ±0.13mm
Static Load:	ASTM F970 - Passes, modified - 1500 psi
Residual Indentation:	ASTM F1914 - Passes - Average less than 8%
Slip Resistance:	ASTM D2047 - Passes - > 0.6 Wet, 0.6 Dry
Resistance To Chemicals:	ASTM F925 - Passes - No Change or Slight Change
Resistance To Heat:	ASTM F1514 - Passes - ΔE ≤ 8
Resistance To Light:	ASTM F1515 - Passes - ΔE ≤ 8
Critical Radiant Flux:	ASTM E648 - Passes - ≥ 0.45 watts/cm <sup>2</sup> , Class 1

**SUSTAINABILITY**

Biobased Material Content:	0%
Rapidly Renewable Resource Content:	0%
Certification:	FloorScore® certified

**SERVICE**

Warranties:	Limited 10 Year Commercial
-------------	----------------------------

Global Entry Collection



378  
Chocolate Bar



976  
Blackout



959  
Grey Granite



927  
Sonic Silver



926  
Agreeable Grey



915  
Frostbite