

Hot and Heavy Collection



DESIGN

Product Type:	Floating LVT
Gauge:	.20"(5mm)
Wear Layer:	20 mil (0.5mm)
Finish:	M-Force Enhanced Urethane
Surface Profile:	Wood Emboss; Light Emboss
Edge Profile:	Bevel
Size:	9"W x 59"L
Square Feet Per Carton:	22.84 sf/ctn (2.12 m ² /ctn)
Pieces Per Carton:	6 pieces/ctn
Pounds per carton:	40.78 lbs/ctn (18.49 kg/ctn)
Installation Method:	Loose Lay with Perimeter Glue
Recommended Adhesive:	MS160 Spray Adhesive or M95.0 Resilient Flooring Adhesive

PERFORMANCE

Construction:	Commercial Grade Loose Lay Enhanced Resilient Tile
Classification:	ASTM F1700 - Class III, Type A - Smooth, Type B - Embossed
Squareness:	ASTM 2421/ASTM F2055 - Passes - ± 0.10 in. max
Size and Tolerance:	ASTM 2421/ASTM F2055 - Passes - ± 0.16 in. per linear foot
Thickness:	ASTM F386 - Passes - as specified ± 0.005 in.
Flexibility:	ASTM F137 - Passes - 1" mandrel
Dimensional Stability:	ASTM F2199 - Passes - 0.020 in. per linear foot
Static Load:	ASTM F970 - Passes, modified - 1000 psi
Residual Indentation:	ASTM F1914 - Passes - Average less than 8%, maximum single read 10%
Slip Resistant:	ASTM D2047 - Passes Wet: ≥ 0.5
Resistance To Chemicals:	ASTM F925 - Passes - No Change or Slight Change
Resistance To Light:	ASTM F1515 - Passes - $\Delta E \leq 16$
Resistance To Heat:	ASTM F1514 - Passes - $\Delta E \leq 16$
Critical Radiant Flux:	ASTM E648 - Passes - ≥ 0.45 watts/cm ² , Class 9
Smoke Density:	ASTME662 - Part A - less than 450
Impact Insulation Class:	57

SUSTAINABILITY


Certification:	FloorScore® certified
Pre Consumer RC:	37%
Post Consumer RC:	22%

SERVICE


Warranties:	Limited 10 Year Commercial
-------------	----------------------------



123
Benmore



142
Kew Gardens




148
Atwell Mill




152
Arrowhead Creek



833
Oakbark



872
Picton Park



878
Woodland



936
Converse Basin



946
Open Canyon

Hot and Heavy Collection



989
Calaveras