Mohawk Group

C0058 Matter

Mass Appeal Collection

134
Raffia

839
Portobello

338
Gingersnap

565
Commodore

917
Ferrous

999
Black Ribbon

DESIGN

Product Type:	**Floating LVT**
Gauge:	**.20" (5mm)**
Wear Layer:	**20 mil**
Finish:	**M-Force Enhanced Urethane**
Size:	**18" x 36"**
Anti-Microbial:	**No**
Installation:	**Perimeter Glue**
Square Feet Per Carton:	**18 sf/ctn**
Pieces Per Carton:	**4 pcs/ctn**

PERFORMANCE

Construction:	**Commercial Grade Loose Lay Resilient Tile**
Classification:	**ASTM F1700 - Class III, Type A - Smooth, Type B - Embossed**
Squareness:	**ASTM F2055 - Passes - 0.010 in. max**
Size and Tolerance:	**ASTM F2055 - Passes - ±0.016 in. per linear foot**
Dimensional Stability:	**ASTM F2199 - Passes - ≤ 0.024 in. per linear foot**
Thickness:	**ASTM F386 - Passes - as specified ±0.005 in. (±0.13 mm)**
Flexibility:	**ASTM F137 - Passes - ≤ 1.0 in., no cracks or breaks**
Residual Indentation:	**ASTM F1914 - Passes - Average less than 8%**
Slip Resistance:	**ASTM C1028 - Passes**
Resistance To Chemicals:	**ASTM F925 - Passes - No Change or Slight Change**
Resistance To Heat:	**ASTM F1514 - Passes - ΔE ≤ 8**
Resistance To Light:	**ASTM F1515 - Passes - ΔE ≤ 8**
Critical Radiant Flux:	**ASTM E648 - Passes - ≥ 0.45 watts/cm2, Class 1**

SUSTAINABILITY

Biobased Material Content:	**0%**
Rapidly Renewable Resource Content:	**0%**
Certification:	**FloorScore® Certificate**

SERVICE

Warranties:	**Limited 10 Year Commercial**