



DESIGN

Product Type:	Floating LVT
Gauge:	.20" (5mm)
Wear Layer:	20 mil
Finish:	M-Force Enhanced Urethane
Size:	18" x 36"
Anti-Microbial:	No
Installation:	Perimeter Glue
Square Feet Per Carton:	18 sf/ctn
Pieces Per Carton:	4 pcs/ctn

PERFORMANCE


Construction:	Commercial Grade Loose Lay Resilient Tile
Classification:	ASTM F1700 - Class III, Type A - Smooth, Type B - Embossed
Squareness:	ASTM F2055 - Passes - 0.010 in. max
Size and Tolerance:	ASTM F2055 - Passes - ±0.016 in. per linear foot
Dimensional Stability:	ASTM F2199 - Passes - ≤ 0.024 in. per linear foot
Thickness:	ASTM F386 - Passes - as specified ±0.005 in. (±0.13 mm)
Flexibility:	ASTM F137 - Passes - ≤ 1.0 in., no cracks or breaks
Residual Indentation:	ASTM F1914 - Passes - Average less than 8%
Slip Resistance:	ASTM C1028 - Passes
Resistance To Chemicals:	ASTM F925 - Passes - No Change or Slight Change
Resistance To Heat:	ASTM F1514 - Passes - ΔE ≤ 8
Resistance To Light:	ASTM F1515 - Passes - ΔE ≤ 8
Critical Radiant Flux:	ASTM E648 - Passes - ≥ 0.45 watts/cm2, Class 1

SUSTAINABILITY

Biobased Material Content:	0%
Rapidly Renewable Resource Content:	0%
Certification:	FloorScore® Certified

SERVICE

Warranties:	Limited 10 Year Commercial
-------------	----------------------------



132
Golden Yellow



258
Viva Gold



268
My Precious



353
Rave Red




464
Vogue Violet



525
Freshwater Blue



556
Tempo Teal



631
Lemon Lime



959
So Fetch

Mass Appeal Collection



929
Paper Gray



859
On The Line



585
Blue Steel