


DESIGN

Product Type:	Rubber
Gauge:	3.17MM (1/8")
Size:	35 11/16" x 35 11/16", 17 13/16"x17 13/16"
Anti-Microbial:	Yes
Installation:	Glue Down
Recommended Adhesive:	Mohawk AD777 - Regular Traffic, Mohawk 530SF - Heavy Rolling Loads, Mohawk 529SF - 2 Part Epoxy

PERFORMANCE






Construction:	Homogeneous
Classification:	ASTM F 1344 - Class 1, A or B
Smoke Density:	ASTM E 662 - ≤ 450
Static Load:	1,100 PSI (modified)
Abrasion Resistance:	ASTM D 3389 - <1 (H 18, 500g @ 1000 cycles)
Resistance To Chemicals:	ASTM F 925 - Compliance
Resistance To Heat:	ASTM F 1514 - $\Delta E < 8.0$
Resistance To Light:	ASTM F 1515 - $\Delta E < 8.0$ (300 hours)
Critical Radiant Flux:	ASTM E 648 - > 0.45

SUSTAINABILITY

Rapidly Renewable Resource Content:	0%
Certification:	FloorScore® Certificate

SERVICE

Warranties:	Limited 10 Year Commercial
-------------	----------------------------


 MCA123
Midnight Charcoal

 MCA189
Emerald Luster

 MCA133
Polished Pewter

 MCA137
Carriage Gray

 MCA191
Night Sky