

Reroot Collection



**DESIGN**

---

Product Type:	Commercial Hardwood
Gauge:	1/2" Thickness
Wear Layer:	2.0mm
Finish:	Enhanced Urethane Finish with Aluminum Oxide
Size:	7" W x 18" to 72" L (Random lengths)
Square Feet Per Carton:	35.04 sf/ctn
Trim and Moldings:	Color coordinating pre-finished trims and moldings: reducer strip, stair nose, baby threshold, t-molding and quarter round
Installation Method:	Glue Down or Nail. Float with Tongue and Groove adhesive over SilentGuard underlayment
Recommended Adhesive:	M908 Pro-Tack Urethane Hardwood Adhesive, M1000 UltraTack 3-in-1 Adhesive for enhanced acoustics and high moisture slabs, GLU1/Eurobond Tongue and Groove adhesive for use when floating
Underlayment:	SilentGuard
Grade Level:	All

**PERFORMANCE**


---

Construction:	Engineered Commercial Hardwood
Flame Spread:	ASTM E648. Class II rating
Smoke Density:	ASTM E662, 450 or less


**SUSTAINABILITY**

---


Certification:	FloorScore® certified
CARB II Compliant:	Yes
Lacey Act Compliant:	Yes



07  
Red Oak



08  
Shadow Oak



79  
Weathered Oak