


Reroot Collection



DESIGN

Product Type:	Commercial Hardwood
Gauge:	1/2" Thickness
Wear Layer:	2.0mm
Finish:	Enhanced Urethane Finish with Aluminum Oxide
Size:	5" W X 11"-48" (Random lengths)
Square Feet Per Carton:	19.7 sf/ctn
Trim and Moldings:	Color coordinating pre-finished trims and moldings: reducer strip, stair nosing, baby threshold, t-molding, wall base and quarter round
Installation Method:	Glue Down or Nail. Float with Tongue and Groove adhesive over SilentGuard underlayment
Recommended Adhesive:	M908 - UltraTac Hardwood Adhesive for enhanced acoustics and high moisture slabs, M1000 - for enhanced acoustics and high moisture slabs, D3/Type II Eurobond - Tongue and Groove adhesive for use when floating
Underlayment:	SilentGuard
Grade Level:	All

PERFORMANCE


Construction:	Engineered Commercial Hardwood
Flame Spread:	ASTM E648, Class II rating
Smoke Density:	ASTM E662, 450 or less

SUSTAINABILITY


Certification:	FloorScore® certified
Lacey Act Compliant:	Yes

SERVICE


Warranties:	5 Year Light Commercial
-------------	-------------------------



76
Onyx Maple



40
Saddle Oak



01
Honey Maple