

Reroot Collection



DESIGN

Product Type:	Commercial Hardwood
Gauge:	9/16" Thickness
Wear Layer:	3.2mm
Finish:	Enhanced Urethane Finish with Aluminum Oxide
Size:	7.48" W x 71.5" L
Square Feet Per Carton:	22.3 sf/ctn
Trim and Moldings:	Color coordinating pre-finished trims and moldings: reducer strip, stair nose, baby threshold, t-molding and quarter round
Installation Method:	Uniclic Multi-Fit Locking System float over SilentGuard underlayment, Glue, nail, staple
Recommended Adhesive:	M908 Pro-Tack Urethane Hardwood Adhesive, M1000 UltraTack 3-in-1 Adhesive for enhanced acoustics and high moisture slabs
Underlayment:	SilentGuard
Grade Level:	All

PERFORMANCE

Construction:	Engineered Commercial Hardwood
Flame Spread:	ASTM E648, Class II rating
Smoke Density:	ASTM E662, 450 or less

SUSTAINABILITY

Certification:	FloorScore® certified
CARB II Compliant:	Yes
Lacey Act Compliant:	Yes

SERVICE

Warranties:	5 Year Light Commercial
-------------	-------------------------




09
Mystic Oak




74
Supernatural Oak




75
Saddle Oak



76
Chestnut Oak



78
Espresso Oak



79
Coastal Oak