



DESIGN


Product Type:	Rubber
Gauge:	2MM(0.080") / 3MM(0.118")
Size:	5'Wx50'L (1.5m x 15.2m)
Anti-Microbial:	Yes
Installation:	Glue Down
Recommended Adhesive:	Mohawk AD777 - Regular Traffic, Mohawk 530SF - Heavy Rolling Loads, Mohawk 529SF - 2 Part Epoxy

PERFORMANCE

Construction:	Homogeneous
Classification:	ASTM F 1344 - Class 1, A or B
Smoke Density:	ASTM E 662 - ≤ 450
Static Load:	ASTM F 970 (modified at 2,000 psi) - ≤0.005"
Abrasion Resistance:	ASTM D 3389 - <1 (H 18, 500g @ 1000 cycles)
Resistance To Chemicals:	ASTM F 925 - Compliance
Resistance To Heat:	ASTM F 1514 - ΔE < 8.0
Resistance To Light:	ASTM F 1515 - ΔE < 8.0 (300 hours)
Critical Radiant Flux:	ASTM E 648 - > 0.45

SUSTAINABILITY

Rapidly Renewable Resource Content:	0%
Certification:	FloorScore® Certificate



TRS2-02
Night Skies



TRS2-03
Sand Bar




TRS2-09
Bubbles



TRS2-13
Pebble



TRS2-14
Canvas




TRS2-15
Cloak



TRS2-23
Mountain Path



TRS2-25
Pottery Clay



TRS2-27
Lemon Icebox


TRUE Medi-Flex Collection




TRS2-29
Gemstone




TRS2-32
Coal



TRS2-33
Dried Coral




TRS2-35
Roma



TRS2-37
Cheddar




TRS2-38
Green Apple




TRS2-43
Freeze



TRS2-47
Warm Sunshine



TRS2-49
Delphinium




TRS2-51
Hail Storm



TRS2-93
In-Service




TRS2-89
Blue Spring




TRS2-86
Violet



TRS2-85
Latte




TRS2-83
Gunmetal



TRS2-78
Spring Valley




TRS2-75
Pecan



TRS2-73
Aircraft Carrier




TRS2-66
Impatience




TRS2-65
Grape Vine




TRS2-63
Buff



TRS2-59
Iris



TRS2-58
Chartreuse



TRS2-57
Orange Sherbet



TRS2-55
Red Hot



TRS2-54
Grain



TRS2-53
Dove