

TRUE Textured Tile Collection



DESIGN

Product Type:	Rubber
Gauge:	3mm /(0.188")
Size:	17 13/16"x17 13/16" (452mm x 452mm) 35 11/16" x 35 11/16" (905mm x 905mm)
Installation Method:	Glue Down
Recommended Adhesive:	Mohawk Ad-777 Adhesive - Regular Traffic, Mohawk AD-535 Epoxy - Heavy Rolling Loads

PERFORMANCE

Construction:	Homogeneous
Classification:	ASTM F 1344 - Rubber Tile, Class 1, A or B
Hardness:	ASTM D 2240 - Shore A \geq 85
Static Load:	ASTM F 970 (modified at 1,000 psi) - \leq 0.005"
Abrasion Resistance:	ASTM D 3389 - Passes (H 18, 500g @ 1000 cycles)
Resistance To Chemicals:	ASTM F 925 - Exceeds
Resistance To Light:	ASTM F 1515 - $\Delta E \leq$ 8.0
Resistance To Heat:	ASTM F 1514 - $\Delta E \leq$ 8.0
Critical Radiant Flux:	ASTM E 648 - $>$ 0.45
Smoke Density:	ASTM E 662 - \leq 450

SUSTAINABILITY

Certification:	FloorScore® certified
Pre Consumer RC:	10%

SERVICE


Warranties:	Limited 10 Year Commercial, Limited 10 Year Colorfast Warranty
-------------	--



02
Night Skies



03
Sandbar




09
Bubbles



13
Pebble



14
Canvas



15
Cloak



23
Mountain Path



25
Pottery Clay




27
Lemon Icebox

TRUE Textured Tile Collection



29
Gemstone



32
Coal



33
Dried Coral



35
Roma




37
Cheddar




38
Green Apple



43
Freeze



47
Warm Sunshine



49
Delphinium



51
Hail Storm



53
Dove




54
Grain



55
Red Hot



57
Orange Sherbet




58
Chartreuse



59
Iris




63
Buff



65
Grape Vine



66
Impatience



73
Aircraft Carrier



75
Pecan




78
Spring Valley




83
Gunmetal




85
Latte



86
Violet



89
Blue Spring



93
In-Service