



DESIGN

Product Type:	Rubber
Gauge:	3mm /(0.188")
Size:	35 11/16" x 35 11/16", 17 13/16"x17 13/16"
Anti-Microbial:	No
Installation:	Glue Down
Recommended Adhesive:	Mohawk AD777 - Regular Traffic, Mohawk 530SF - Heavy Rolling Loads, Mohawk 529SF - 2 Part Epoxy

PERFORMANCE


Construction:	Homogeneous
Classification:	ASTM F 1344 - Class 1, A or B
Smoke Density:	ASTM E 662 - ≤ 450
Static Load:	ASTM F 970 (modified at 1,100 psi) - ≤0.005"
Abrasion Resistance:	ASTM D 3389 - <1 (H 18, 500g @ 1000 cycles)
Resistance To Chemicals:	ASTM F 925 - Compliance
Resistance To Heat:	ASTM F 1514 - ΔE < 8.0
Resistance To Light:	ASTM F 1515 - ΔE <8.0 (300 hours)
Critical Radiant Flux:	ASTM E 648 - > 0.45

SUSTAINABILITY


Rapidly Renewable Resource Content:	0%
Certification:	FloorScore® Certified

SERVICE

Warranties:	Limited 10 Year Commercial, Limited 10 year Colorfast Warranty
-------------	--



TRA-32
Coal




TRA-63
Buff



TRA-85
Latte



TRA-89
Blue Spring



TRA-93
In-Service