

TRUE Textured Tile Collection



DESIGN

Product Type:	Rubber
Gauge:	3mm (0.188")
Size:	35 11/16" x 35 11/16", 17 13/16"x17 13/16"
Installation Method:	Glue Down
Recommended Adhesive:	Mohawk Ad-777 Adhesive - Regular Traffic, Mohawk AD-535 Epoxy - Heavy Rolling Loads

PERFORMANCE


Construction:	Homogeneous
Classification:	ASTM F 1344 - Rubber Tile, Class 1, A or B
Hardness:	ASTM D 2240 - Shore A ≥ 85
Static Load:	ASTM F 970 (modified at 1,000 psi) - ≤0.005"
Abrasion Resistance:	ASTM D 3389 - Passes (H 18, 500g @ 1000 cycles)
Resistance To Chemicals:	ASTM F 925 - Exceeds
Resistance To Light:	ASTM F 1515 - ΔE ≤8.0
Resistance To Heat:	ASTM F 1514 - ΔE ≤8.0
Critical Radiant Flux:	ASTM E 648 - > 0.45
Smoke Density:	ASTM E 662 - ≤ 450

SUSTAINABILITY

Certification:	FloorScore® certified
Pre Consumer RC:	10%

SERVICE

Warranties:	Limited 10 Year Commercial, Limited 10 Year Colorfast Warranty
-------------	---



32
Coal




63
Buff



85
Latte



89
Blue Spring



93
In-Service