

TRUE Textured Tile Collection



DESIGN

| | |
|-----------------------|--|
| Product Type: | Rubber |
| Gauge: | 3mm (0.188") |
| Size: | 17 13/16"x17 13/16" (452mm x 452mm) 35 11/16" x 35 11/16" (905mm x 905mm) |
| Installation Method: | Glue Down |
| Recommended Adhesive: | Mohawk Ad-777 Adhesive - Regular Traffic, Mohawk AD-535 Epoxy - Heavy Rolling Loads |

PERFORMANCE


| | |
|--------------------------|---|
| Construction: | Homogeneous |
| Classification: | ASTM F 1344 - Rubber Tile, Class 1, A or B |
| Hardness: | ASTM D 2240 - Shore A ≥ 85 |
| Static Load: | ASTM F 970 (modified at 1,000 psi) - ≤0.005" |
| Abrasion Resistance: | ASTM D 3389 - Passes (H 18, 500g @ 1000 cycles) |
| Resistance To Chemicals: | ASTM F 925 - Exceeds |
| Resistance To Light: | ASTM F 1515 - ΔE ≤8.0 |
| Resistance To Heat: | ASTM F 1514 - ΔE ≤8.0 |
| Critical Radiant Flux: | ASTM E 648 - > 0.45 |
| Smoke Density: | ASTM E 662 - ≤ 450 |

SUSTAINABILITY

| | |
|------------------|-----------------------|
| Certification: | FloorScore® certified |
| Pre Consumer RC: | 10% |

SERVICE

| | |
|-------------|--|
| Warranties: | Limited 10 Year Commercial, Limited 10 Year Colorfast Warranty |
|-------------|--|



32
Coal



63
Buff



85
Latte



89
Blue Spring



93
In-Service