



DESIGN

Product Type:	Floating LVT
Gauge:	0.118" (3mm)
Wear Layer:	12mil/0.3mm
Finish:	UV-Cured Commercial Grade Urethane
Size:	6"x36" planks with 12"x36" Underlay
Anti-Microbial:	No
Installation:	Peel and Stick LVT with Floating Underlay
Recommended Adhesive:	None Required
Square Feet Per Carton:	24 sq ft/ctn (2.22 m ²)
Pieces Per Carton:	16 (plank), 8 (underlay) pcs/ctn
Pounds per carton:	46 lbs/ctn (20.86 kg/ctn)

PERFORMANCE


Construction:	Luxury Vinyl Tile with underlay
Classification:	ASTM F-1700 - Class III, Type A - Smooth, Type B - Embossed
Smoke Density:	ASTM E662 - Passes - < 450
Impact Insulation Class:	59
Squareness:	ASTM F2055 -10 Passes - maximum 0.010 in. (0.25mm)
Size and Tolerance:	ASTM F2055 - Passes - at ±0.016 in./lin. Ft. (0.4 mm/305 mm)
Dimensional Stability:	ASTM F2199 - Passes - no greater than 0.020 in./lin. Ft. (0.51 mm/305 mm)
Thickness:	ASTM F386 - Passes - as specified ±0.005 in. (0.13 mm)
Flexibility:	ASTM F137 - Passes - 1 in. (25.4-mm mandrel, no crack or break)
Static Load:	ASTM F970 - Passes - Exceeds 250 psi
Residual Indentation:	ASTM F1914 - Passes - average less than 8%
Slip Resistance:	ADA Compliant - > 0.6
Resistance To Chemicals:	ASTM F925 - Passes - no change
Resistance To Heat:	ASTM F1514 - Passes - less than 8 ave., max
Resistance To Light:	ASTM F1515 - Passes - less than 8 ave., max
Critical Radiant Flux:	ASTM E648 - Passes - > 0.45 watts/cm ² , Class 1

SUSTAINABILITY


Rapidly Renewable Resource Content:	0%
Certification:	FloorScore® Certificate

SERVICE


Warranties:	Limited 10 Year Commercial
-------------	----------------------------



10 Sugar Maple 11 Royal Forest 20 American Cherry



21 Praline 31 Barnwood 40 Warm Maple



41 Nutshell 50 Natural Teak 51 Aged Oak

Active Tec Collection



60
English Walnut



61
Coastal Dunes



70
Warm Timber



80
Atlas Cedar



90
Heritage Cedar