

DESIGN

Product Type:	Commercial Hardwood
Overall Thickness:	3/8" Thickness
Wear Layer:	2 mm
Finish:	Enhanced Urethane Finish with Aluminum Oxide
Size:	3"W and 5"W x random lengths
Square Feet Per Carton:	28.25 sf/ctn
Installation Method:	Glue, nail, staple, or float; float with tongue and groove adhesive over SilentGuard underlayment
Recommended Adhesive:	M92X Modified Moisture-Cured Urethane Adhesive, M1000 - for enhanced acoustics and high moisture slabs, D3/Type II Eurobond - Tongue and Groove adhesive for use when floating
Underlayment:	SilentGuard

PERFORMANCE


Construction:	Engineered Commercial Hardwood
Flame Spread:	ASTM E648. Class II rating
Smoke Density:	ASTM E662, 450 or less

SUSTAINABILITY


Certification:	FloorScore® certified
CARB II Compliant:	Yes
Lacey Act Compliant:	Yes
Country of Origin:	Made In USA

SERVICE


Warranties:	5 Year Light Commercial
-------------	-------------------------




10
Pure Maple Natural




12
Coffee Maple




24
Crema Maple




25
Sable Hickory




41
Flint Maple



50
Oak Gunstock



75
Gunpowder Hickory



97
Oak Shale