



DESIGN

Product Type:	Commercial Hardwood
Gauge:	3/8" Thickness
Wear Layer:	2mm
Finish:	Enhanced Urethane Finish with Aluminum Oxide
Species:	Maple
Size:	2.25", 3.25"W and 5"W x random lengths
Square Feet Per Carton:	28.25 sf/ctn
Installation Method:	Glue, nail, staple, or float; float with tongue and groove adhesive over SilentGuard underlayment
Recommended Adhesive:	M908 ProTack Urethane Hardwood Adhesive, M1000 UltraTack Advanced 3-in-1 Adhesive for enhanced acoustics and high moisture slabs
Underlayment:	SilentGuard

PERFORMANCE


Construction:	Engineered Commercial Hardwood
Flame Spread:	ASTM E648. Class II rating
Smoke Density:	ASTM E662, 450 or less

SUSTAINABILITY


Certification:	FloorScore® certified
CARB II Compliant:	Yes
Lacey Act Compliant:	Yes
Country of Origin:	Made In USA

SERVICE


Warranties:	5 Year Light Commercial
-------------	-------------------------




50
Oak Gunstock




97
Oak Shale




10
Pure Maple Natural




24
Crema Maple




41
Flint Maple



12
Coffee Maple



25
Sable Hickory



75
Gunpowder Hickory