



DESIGN

Product Type:	Floating LVT
Gauge:	3.2mm
Wear Layer:	12 mil (0.3mm)
Finish:	M-Force Enhanced Urethane
Size:	5.91" x 48.62"
Square Feet Per Carton:	31.9 sf/ctn
Pounds per carton:	47.41 lbs/ctn
Installation Method:	Floating LVT with Uniclic Locking System
Recommended Adhesive:	None Required
Underlayment:	Mohawk ActiveSound

PERFORMANCE


Construction:	Commercial Grade Floating Luxury Vinyl Tile
Classification:	ASTM F1700 - Class III, Type A - Smooth, Type B - Embossed
Squareness:	ASTM F2055 - Passes - 0.010 in. max
Size and Tolerance:	ASTM F2055 - Passes - ±0.016 in. per linear foot
Thickness:	ASTM F386 - Passes - as specified ±0.005 in. (±0.13 mm)
Flexibility:	ASTM F137 - Passes - ≤ 1.0 in., no cracks or breaks
Dimensional Stability:	ASTM F2199 - Passes - 0.15% max (0.020 in. per linear foot)
Residual Indentation:	ASTM F1914 - Passes - Average less than 8%
Slip Resistant:	ASTM C1028 - Passes - ≥ 0.5
Resistance To Chemicals:	ASTM F925 - Passes - No Change
Resistance To Light:	ASTM F1515 - Passes - ΔE ≤ 8
Resistance To Heat:	ASTM F1514 - Passes - ΔE ≤ 8
Critical Radiant Flux:	ASTM E648 - Passes - ≥ 0.45 watts/cm2, Class 1
Smoke Density:	ASTM E662 - Passes - < 450

SUSTAINABILITY


Certification:	FloorScore® certified
----------------	------------------------------

SERVICE

Warranties:	Limited 10 Year Light Commercial
-------------	---



233
Gally Gold



242
Honeytone



258
Realist



262
Pier



717
Winter White



822
Blondie



857
Woodridge



872
Bombay



881
Armoire



988
Key-Note