



**DESIGN**

Product Type:	<b>Floating LVT</b>
Gauge:	<b>3.2mm</b>
Wear Layer:	<b>12 mil (0.3mm)</b>
Finish:	<b>M-Force Enhanced Urethane</b>
Size:	<b>5.91"W x 48.62"L</b>
Square Feet Per Carton:	<b>31.9 sf/ctn</b>
Pounds per carton:	<b>47.41 lbs/ctn</b>
Installation Method:	<b>Floating LVT with Uniclic Locking System</b>
Recommended Adhesive:	<b>None Required</b>
Underlayment:	<b>Mohawk ActiveSound</b>

**PERFORMANCE**


Construction:	<b>Commercial Grade Floating Luxury Vinyl Tile</b>
Classification:	<b>ASTM F1700 - Class III, Type A - Smooth, Type B - Embossed</b>
Squareness:	<b>ASTM F2055 - Passes - 0.010 in. max</b>
Size and Tolerance:	<b>ASTM F2055 - Passes - ±0.016 in. per linear foot</b>
Thickness:	<b>ASTM F386 - Passes - as specified ±0.005 in. (±0.13 mm)</b>
Flexibility:	<b>ASTM F137 - Passes - ≤ 1.0 in., no cracks or breaks</b>
Dimensional Stability:	<b>ASTM F2199 - Passes - 0.15% max (0.020 in. per linear foot)</b>
Residual Indentation:	<b>ASTM F1914 - Passes - Average less than 8%</b>
Slip Resistant:	<b>ASTM C1028 - Passes - ≥ 0.5</b>
Resistance To Chemicals:	<b>ASTM F925 - Passes - No Change</b>
Resistance To Light:	<b>ASTM F1515 - Passes - ΔE ≤ 8</b>
Resistance To Heat:	<b>ASTM F1514 - Passes - ΔE ≤ 8</b>
Critical Radiant Flux:	<b>ASTM E648 - Passes - ≥ 0.45 watts/cm2, Class 1</b>
Smoke Density:	<b>ASTM E662 - Passes - &lt; 450</b>

**SUSTAINABILITY**


Certification:	<b>FloorScore® certified</b>
----------------	------------------------------

**SERVICE**

Warranties:	<b>Limited 10 Year Light Commercial</b>
-------------	---



233  
Gally Gold



242  
Honeytone



258  
Realist



262  
Pier



717  
Winter White



822  
Blondie



857  
Woodridge



872  
Bombay



881  
Armoire



988  
Key-Note