



DESIGN

Product Type:	Floating LVT
Gauge:	3.2mm
Wear Layer:	12 mil
Finish:	M-Force Enhanced Urethane
Size:	6" x 48" (Nominal)
Anti-Microbial:	No
Installation:	Floating LVT with Uniclic Locking System
Recommended Adhesive:	None Required
Square Feet Per Carton:	31.9 sf/ctn
Pounds per carton:	47.41 lbs/ctn
Underlayment:	Mohawk ActiveSound

PERFORMANCE


Construction:	Commercial Grade Floating Luxury Vinyl Tile
Classification:	ASTM F1700 - Class III, Type A - Smooth, Type B - Embossed
Smoke Density:	ASTM E662 - Passes - < 450
Squareness:	ASTM F2055 - Passes - 0.010 in. max
Size and Tolerance:	ASTM F2055 - Passes - ±0.016 in. per linear foot
Dimensional Stability:	ASTM F2199 - Passes - 0.15% max (0.020 in. per linear foot)
Thickness:	ASTM F386 - Passes - as specified ±0.005 in. (±0.13 mm)
Flexibility:	ASTM F137 - Passes - ≤ 1.0 in., no cracks or breaks
Residual Indentation:	ASTM F1914 - Passes - Average less than 8%
Slip Resistance:	ASTM C1028 - Passes - ≥ 0.5
Resistance To Chemicals:	ASTM F925 - Passes - No Change
Resistance To Heat:	ASTM F1514 - Passes - ΔE ≤ 8
Resistance To Light:	ASTM F1515 - Passes - ΔE ≤ 8
Critical Radiant Flux:	ASTM E648 - Passes - ≥ 0.45 watts/cm ² , Class 1

SUSTAINABILITY


Rapidly Renewable Resource Content:	0%
Certification:	FloorScore® Certified

SERVICE

Warranties:	Limited 10 Year Light Commercial
-------------	----------------------------------



233
Gally Gold



242
Honeytone



258
Realist




262
Pier



717
Winter White



822
Blondie



857
Woodridge



872
Bombay



881
Armoire



988
Key-Note