



**DESIGN**

Tufted Pile Weight:	20.0 oz. per sq. yd. (678 g/m <sup>2</sup> )
Product Type:	Tile
Construction:	Tufted
Minimum Sq. Yd.:	No Minimum
Surface Texture:	Textured Patterned Loop
Gauge:	1/12 (47.00 rows per 10 cm)
Density:	6,428
Weight Density:	128,571
Stitches Per Inch:	11.0 (43.31 per 10 cm)
Finished Pile Thickness:	.112" (2.84 mm)
Dye Method:	Solution Dyed
Backing Material:	EcoFlex NXT
Fiber Type:	Duracolor® Tricolor Premium Nylon with metallic Duracolor
Fiber Technology:	Duracolor® by Mohawk Group's Stain Resistant System. Passes GSA requirements for permanent stain resistant carpet.
Pattern Repeat:	Not Applicable
Size:	24" x 24" (.6096 m x .6096 m)
Installation Method:	Quarter Turn, Monolithic, Brick Ashlar, Vertical Ashlar, Multi Directional
GSA Stain Release Rating:	Pass
Stain Release Technology:	Permanent, Built into Fiber
Soil Release Technology:	Sentry Soil Protection
Foot Traffic Recommendation TARR:	Severe

**SUSTAINABILITY**

IAQ Green Label Plus:	CRI Green Label Plus GLP1171
Pre-Consumer Recycled Content:	56%
NSF 140:	EcoFlex NXT - NSF 140 Gold
Declare Label:	Declared Red List Free

**PERFORMANCE**

Static:	AATCC-134 Under 3.5 KV
Flammability:	ASTM E 648 Class 1 (Glue Down)
Smoke Density:	ASTM E 662 Less than 450

**SERVICE**

Warranties:	Lifetime Limited Carpet Tile Warranty, Lifetime Duracolor Stain Warranty, Lifetime Static
-------------	---



138  
Sulpher  
Quickship Available



576  
Lagoon  
Quickship Available



739  
Glacier  
Quickship Available



856  
Sediment  
Quickship Available



869  
Alpine  
Quickship Available



949  
Fossil  
Quickship Available



955  
Coastal  
Quickship Available



978  
Mineral  
Quickship Available