




T002M
Sea Salt




T003M
Tea Tin




T005M
Earl Gray




T001M
Bronze Kona




T004M
Cast Iron




T007M
Pearl Cloud



T016M
Artisan White



T012M
Light Mocha



T010M
Imperial Gray

DESIGN

Product Type:	Glue Down LVT
Gauge:	0.118" (3mm)
Wear Layer:	20 mil (0.5mm)
Finish:	M-Force Enhanced Urethane
Size:	18" x 36"
Anti-Microbial:	No
Installation:	Glue Down
Recommended Adhesive:	M95.0 Resilient Flooring Adhesive, MS160 Spray, M700 Pressure Sensitive Adhesive
Square Feet Per Carton:	36 sf/ctn (3.34 m ² /ctn)
Pieces Per Carton:	8 pcs/ctn
Pounds per carton:	42 lbs/ctn (19.05 kg/ctn)
Underlayment:	Mohawk Accusound

PERFORMANCE

Construction:	Commercial Grade Resilient Tile
Classification:	ASTM F1700 - Class III, Type A - Smooth, Type B - Embossed
Smoke Density:	ASTM E662 - Passes - < 450
Squareness:	ASTM F2055 - Passes - 0.010 in. max
Size and Tolerance:	ASTM F2055 - Passes - ±0.016 in. per linear foot
Dimensional Stability:	ASTM F2199 - Passes - ≤ 0.020 in. per linear foot
Thickness:	ASTM F386 - Passes - As specified ±0.005 in.
Static Load:	ASTM F970 - Passes, modified - 1500 psi
Residual Indentation:	ASTM F1914 - Passes - Average less than 8%
Slip Resistance:	ASTM D2047 - Passes - > 0.6 Wet, 0.6 Dry
Resistance To Chemicals:	ASTM F925 - Passes - No Change
Resistance To Heat:	ASTM F1514 - Passes - ΔE ≤ 8
Resistance To Light:	ASTM F1515 - Passes - ΔE ≤ 8
Critical Radiant Flux:	ASTM E648 - Passes - ≥ 0.45 watts/cm ² , Class 1

SUSTAINABILITY

Rapidly Renewable Resource Content:	0%
Certification:	FloorScore® certified


SERVICE

Warranties:	Limited 10 Year Commercial
-------------	----------------------------

Select Step Collection



T014M
Thai Mountain



T009M
Azteca