

Select Step Collection



DESIGN

Product Type:	Glue Down LVT
Gauge:	0.118" (3mm)
Wear Layer:	20 mil (0.5mm)
Finish:	M-Force Enhanced Urethane
Size:	18"W x 36"L (457.2 mm x 914.4 mm)
Square Feet Per Carton:	36 sf/ctn (3.34 m ² /ctn)
Pieces Per Carton:	8 pieces/ctn
Pounds per carton:	42 lbs/ctn (19.05 kg/ctn)
Installation Method:	Glue Down
Recommended Adhesive:	M95.0 Resilient Flooring Adhesive, MS160 Spray, M700 Pressure Sensitive Adhesive
Underlayment:	Mohawk Accusound

PERFORMANCE


Construction:	Commercial Grade Resilient Tile
Classification:	ASTM F1700 - Class III, Type A - Smooth, Type B - Embossed
Squareness:	ASTM F2055 - Passes - 0.010 in. max
Size and Tolerance:	ASTM F2055 - Passes - ±0.016 in. per linear foot
Thickness:	ASTM F386 - Passes - As specified ±0.005 in.
Dimensional Stability:	ASTM F2199 - Passes - ≤ 0.020 in. per linear foot
Static Load:	ASTM F970 - Passes, modified - 1500 psi
Residual Indentation:	ASTM F1914 - Passes - Average less than 8%
Slip Resistant:	ASTM D2047 - Passes - > 0.6 Wet, 0.6 Dry
Resistance To Chemicals:	ASTM F925 - Passes - No Change
Resistance To Light:	ASTM F1515 - Passes - ΔE ≤ 8
Resistance To Heat:	ASTM F1514 - Passes - ΔE ≤ 8
Critical Radiant Flux:	ASTM E648 - Passes - ≥ 0.45 watts/cm ² , Class 1
Smoke Density:	ASTM E662 - Passes - < 450

SUSTAINABILITY


Certification:	FloorScore® certified
----------------	-----------------------

SERVICE


Warranties:	Limited 10 Year Commercial
-------------	----------------------------




T001M
Bronze Kona




T002M
Sea Salt




T003M
Tea Tin




T004M
Cast Iron




T005M
Earl Gray




T007M
Pearl Cloud



T009M
Azteca



T010M
Imperial Gray




T012M
Light Mocha

Select Step Collection



T014M
Thai Mountain



T016M
Artisan White