Mohawk Group

C0007S Stone

Select Step Collection

T009M
Azteca

T012M
Light Mocha

T004M
Cast Iron



T003M
Tea Tin

T014M
Thai Mountain

T010M
Imperial Gray

T016M
Artisan White

T007M
Pearl Cloud

T001M
Bronze Kona

DESIGN

Product Type:	**Glue Down LVT**
Gauge:	**0.118" (3 mm)**
Wear Layer:	**20 mil**
Finish:	**M-Force Enhanced Urethane**
Size:	**18" x 18"**
Anti-Microbial:	**No**
Installation:	**Glue Down**
Recommended Adhesive:	**M95.0 Acrylic, MS160 Spray, M700 Pressure Sensitive Adhesive**
Square Feet Per Carton:	**36 sf/ctn (3.34 m^2/ctn)**
Pieces Per Carton:	**16 pcs/ctn**
Pounds per carton:	**42 lbs/ctn (19.05 kg/ctn**
Underlayment:	**Mohawk Accusound**
Underlayment Adhesive:	**Mohawk M950, M700 or Mohawk's MS160 spray adhesive**

PERFORMANCE

Construction:	**Commercial Grade Resilient Tile**
Classification:	**ASTM F1700 - Class III, Type A - Smooth, Type B - Embossed**
Smoke Density:	**ASTM E662 - Passes - < 450**
Squareness:	**ASTM F2055 - Passes - 0.010 in. max**
Size and Tolerance:	**ASTM F2055 - Passes - ±0.016 in. per linear foot**
Dimensional Stability:	**ASTM F2199 - Passes - ≤ 0.020 in. per linear foot**
Thickness:	**ASTM F386 - Passes - As specified ±0.005 in.**
Static Load:	**ASTM F970 - Passes, modified - 1500 psi**
Residual Indentation:	**ASTM F1914 - Passes - Average less than 8%**
Slip Resistance:	**ASTM D2047 - Passes - > 0.6 Wet, 0.6 Dry**
Resistance To Chemicals:	**ASTM F925 - Passes - No Change**
Resistance To Heat:	**ASTM F1514 - Passes - ΔE ≤ 8**
Resistance To Light:	**ASTM F1515 - Passes - ΔE ≤ 8**
Critical Radiant Flux:	**ASTM E648 - Passes - ≥ 0.45 watts/cm^2, Class 1**

SUSTAINABILITY

Rapidly Renewable Resource Content:	**0%**
Certification:	**FloorScore® Certificate**

SERVICE

Warranties:	**Limited 10 Year Commercial**

T005M
Earl Gray

T002M
Sea Salt