## Mohawk Group

**Select Step Collection** 





P002S Sable Chestnut



P005S Tanned Tassel



P011S Plantation Brown



P009S Rawhide Tan

P007S Brown Shutter



P012S Natural Wheat

P013S

Ginger Snap





Farmhouse Brown

P014S Sorrel

P010S

#### **DESIGN**

Product Type: Glue Down LVT 0.118" (3 mm) Gauge: Wear Layer: 20 mil

Finish: M-Force Enhanced Urethane

7.25" x 48" Size:

Anti-Microbial: No

Installation: Glue Down

M95.0 Acrylic, MS160 Spray, M700 Pressure Recommended Adhesive: Sensitive Adhesive

Square Feet Per Carton: 36.25 sf/ctn (3.36 m<sup>2</sup>/ctn)

Pieces Per Carton: 15 pcs/ctn

Pounds per carton: 42 lbs/ctn (19.05 kg/ctn

Underlayment: Mohawk Accusound

Mohawk M950, M700 or Mohawk's MS160 spray Underlayment Adhesive:

adhesive

#### **PERFORMANCE**

Construction: Commercial Grade Resilient Tile

ASTM F1700 - Class III, Type A - Smooth, Type B -Classification:

ASTM E662 - Passes - < 450 Smoke Density:

Squareness: ASTM F2055 - Passes - 0.010 in. max

ASTM F2055 - Passes - ±0.016 in. per linear foot Size and Tolerance: ASTM F2199 - Passes - ≤ 0.020 in. per linear foot Dimensional Stability: ASTM F386 - Passes - As specified ±0.005 in. Thickness:

Static Load: ASTM F970 - Passes, modified - 1500 psi

ASTM F1914 - Passes - Average less than 8% Residual Indentation: Slip Resistance: ASTM D2047 - Passes - > 0.6 Wet, 0.6 Dry

Resistance To Chemicals: ASTM F925 - Passes - No Change ASTM F1514 - Passes - ∆E ≤ 8 Resistance To Heat: Resistance To Light: ASTM F1515 - Passes - ∆E ≤ 8

Critical Radiant Flux: ASTM E648 - Passes - ≥ 0.45 watts/cm2, Class 1

#### SUSTAINABILITY

Rapidly Renewable Resource

Content:

Certification: FloorScore® Certificate

#### **SERVICE**

Warranties: Limited 10 Year Commercial

# Mohawk Group

### Select Step Collection







P003S Tanned Chestnut



P004S Warm Cider



P001S Barnwood Chestnut



P008S Cottage Gray



P014S Sorrell