

DESIGN

Product Type:	Woven
Construction:	Woven
Minimum Sq. Yd.:	No Minimum
Surface Texture:	Level Patterned Cut and Loop
Density:	5,000
Weight Density:	200,000
Pitch:	135 (197 ends per meter)
Rows Per Inch:	8.8 (34.65 per 10 cm)
Finished Pile Thickness:	.288" (7.32 mm)
Dye Method:	Solution Dyed
Backing Material:	Woven
Fiber Type:	Colorstrand® SD Nylon
Face Weight:	40.0 oz. per sq. yd. (1356 g/m2)
Pattern Repeat:	.40" (W) x .11" (L)
Width:	12' width (3.66 m)
Soil Release Technology:	Sentry Plus
Foot Traffic Recommendation TARR:	Heavy

SUSTAINABILITY

IAQ Green Label Plus:	Green Label Plus 3802
Pre-Consumer Recycled Content:	13.00
NSF 140:	Gold
Declare Label:	Declared Red List Free

PERFORMANCE

Static:	AATCC-134 Under 3.5 KV
Flammability:	ASTM E 648 Class 1 (Glue Down)
Smoke Density:	ASTM E 662 Less than 450

SERVICE

Warranties:	Lifetime Limited Woven Wear Warranty, Lifetime Limited Colorfastness to Light, 10 Year Limited Colorfastness to Atmospheric Contaminants, 10 Year Limited Stain Warranty, Lifetime Static
-------------	--



721 Bisque 733 Ecru 741 Wheat




753 Aztec 836 Khaki 863 Noire



915 Haze 923 Seashell 948 Alloy



954
Slate



968
Pumice



978
Charcoal