





Construction:	Tufted
Density:	4,656
Dye Method:	Solution Dyed
Fiber Type:	EnviroStrand™ PET
Gauge:	1/10 (39.37 rows per 10 cm)
Product Type:	Broadloom
SmokeDensity:	ASTM E 662 Less than 450
Width:	12' width (3.66 m)
Dropped:	No
BackingMaterial:	Weldlok®
FinishedPileThickness:	.118" (3.00 mm)
Flammability:	ASTM E 648 Class 1 (Glue Down)
IAQGreenLabelPlus:	CRI Green Label Plus GLP0350
Pattern:	Tweed
PileRange:	16
Scale:	Medium
RecycledContentTotalWeight:	0.30
RecycledContentPostConsumer:	30%
SoilReleaseTechnology:	EcoSentry Soil Protection
Static:	AATCC-134 Under 3.5 KV
StitchesPerInch:	10.5 (41.34 per 10 cm)
SurfaceTexture:	Textured Patterned Loop
WeightDensity:	74,496
LaunchYear:	2016
Top10Corp:	No
Top10Healthcare:	No
Top10K12:	No
Top10REITI:	No
Top10Gov:	No
Top10SeniorLiving:	No
Top10HigherEd:	No
Top10Retail:	No
Pattern Repeat:	.6" (W) x .5" (L)
Budget:	\$
CountryOfOrigin:	Ships from US
PileThickness:	.118" (3.00 mm)
RedListFree:	No
Post Consumer RC:	30%
FaceWeight:	16.0 oz. per sq. yd. (542 g/m2)



579
Midnight Blue



846
Pebble Stone



968
Natural Neutral



999
Wrought Iron

SERVICE