



**DESIGN**

Product Type:	Broadloom
Construction:	Tufted
Minimum Sq. Yd.:	No Minimum
Surface Texture:	Textured Patterned Loop
Gauge:	1/10 (39.37 rows per 10 cm)
Density:	4,656
Weight Density:	74,496
Stitches Per Inch:	10.5 (41.34 per 10 cm)
Finished Pile Thickness:	.118" (3.00 mm)
Dye Method:	Solution Dyed
Backing Material:	Weldlok®
Fiber Type:	EnviroStrand™ PET
Face Weight:	16.0 oz. per sq. yd. (542 g/m2)
Pattern Repeat:	.6" (W) x .5" (L)
Width:	12' width (3.66 m)
Soil Release Technology:	Sentry Plus
Foot Traffic Recommendation TARR:	Moderate

**SUSTAINABILITY**


IAQ Green Label Plus:	Green Label Plus 0350
Pre-Consumer Recycled Content:	31.00
Post-Consumer Recycled Content:	1.00
Declare Label:	Declared Red List Free

**PERFORMANCE**


Static:	AATCC-134 Under 3.5 KV
Flammability:	ASTM E 648 Class 1 (Glue Down)
Smoke Density:	ASTM E 662 Less than 450

**SERVICE**

Warranties:	10 Year Limited Wear Warranty, 10 Year Limited Static Protection Warranty, 10 Year Stain Resistance Warranty, 10 Year Limited Colorfastness to Light, 10 Year Limited Colorfastness to Atmospheric Contaminants
-------------	---




579  
Midnight Blue



846  
Pebble Stone



858  
Mocha Brown



862  
Ripe Pepper



968  
Natural Neutral



999  
Wrought Iron